

AMERICAS CORE



Descripción del producto

CORE base stocks by ExxonMobil are designed to offer broad blending coverage with performance capabilities in applications ranging from engine oils to industrial lubricants.

Americas CORE base stocks constitute a slate as defined within API/ATIEL Guidelines for formulation and qualification of automotive lubricants.

With base oil interchange and viscosity grade read-across capabilities, ExxonMobil's Americas CORE base stock slate offers broad coverage, enabling supply chain flexibility and simplified qualification testing requirements. ExxonMobil follows rigorous processes to ensure reliable delivery of consistent quality base stocks so customers can be confident in their base stock supply.

Sales Specifications

			CORE 100	CORE 150	CORE 600	CORE 2500
Property	Limit	Standard Method				
Appearance		Visual	BC	BC	BC	BC
ASTM Colour	Max	ASTM D 1500	1.5	1.5	4	6
CCS Viscosity -25°C mPa•seg	Max	ASTM D 5293	1650			
CCS Viscosity -20°C mPa•seg	Max	ASTM D 5293		2100		
Flash Point, COC Deg C	Min	ASTM D 92	194	210	246	294
Kinematic Viscosity@ 40°C mm2/sec	Min-Max	ASTM D 445	18.5-21.0	29.0-32.0	109.0-116.0	
Kinematic Viscosity@ 100°C mm2/sec	Min-Max	ASTM D 445				30.6-32.7
NOACK Volatility wt%	Max	ASTM D 5800	30	20		
Pour Point Deg C	Max	ASTM D 97	-18	-15	-6	-6
Viscosity Index	Min	ASTM D 2270	95	95	95	95

(a) In lieu of standard test method, alternate test methods may be used for the certification of a product property.
 Note 1: Products are certified on release to meet the values specified. Actual values may deviate within the established reproducibility of the test method specified.

Note 2: For purpose of determining conformance with specification, observed or calculated values shall be rounded off to the nearest unit in the last significant digit used in expressing the limiting value in accordance to the ASTM E 29 method

Health and Safety

Detailed health and safety information for this product is provided in the material safety data sheet (MSDS), available upon request through your local sales representative or from www.ExxonMobil.com.

ExxonMobil, the ExxonMobil logotype and CORE are trademarks of Exxon Mobil Corporation or one of its subsidiaries.

ExxonMobil
 3225 Gallows Road
 Fairfax, VA 22037-001
 1-800-662-4592
<http://www.exxonmobil.com>

All products may not be available in all countries. Every care has been taken in the preparation of this information. Typical values may vary within modest ranges and specifications may be subject to change. To the extent permitted by applicable law, all warranties and/or representations, express or implied, as to the accuracy of the information are disclaimed, and no liability is accepted for the accuracy or completeness of the same.

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names which include Esso, Mobil, Exxon, or ExxonMobil. For convenience and simplicity, the term ExxonMobil may be used to represent all of these entities, and the products and services provided by those entities. Nothing in this brochure is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with local ExxonMobil-affiliated entities.

Copyright © 2001-2013 Exxon Mobil Corporation. All rights reserved.